10

15

20

WHAT IS CLAIMED IS:

 A polycarbonate composition comprising a phosphorus compound represented by the general formula (I),

$$R^{1} = (O)_{n} = (O)_{$$

in which

 $R^1,\,R^2,\,R^3$ and R^4 are each independently selected from (i) C_1 to C_8 alkyl optionally substituted by halogen, (ii) C_5 to C_6 cycloalkyl, (iii) C_6 to C_{10} aryl and (iv) C_7 to C_{12} aralkyl, each of (ii), (iii) and (iv) being optionally and independently substituted by at least one of halogen and C_1 to C_4 alkyl;

n is 0 or 1;

q is 0, 1, 2, 3 or 4:

N is 0.1 to 5

 R^{5} and R^{6} are each independently selected from C_{1} to C_{4} alkyl and halogen; and

- Y denotes isopropylidene,
- 25 wherein the phosphorous compound represented by general formula (I) comprises less than 1 wt. % of isopropenylphenyl phosphate, based on the weight of said phosphorus compound represented by formula (I).

15

20

25

30

- 2. The composition of Claim 1, wherein said phosphorous compound represented by general formula (I) comprises less than 0.5 wt. % of isopropylphenyl phosphate, based on the weight of said phosphorus compound represented by general formula (I).
- 3. The composition of Claim 1, wherein said phosphorous compound represented by general formula (I) comprises less than 0.2 wt. % of isopropylphenyl phosphate, based on the weight of said phosphorus compound represented by general formula (I).
- 4. The composition of Claim 1, comprising 0.5 to 20 wt. % of said phosphorus compound represented by general formula (I) or a mixture of phosphorus compounds represented by general formula (I), based on the total weight of said composition.
- The composition of Claim 1, further comprising 0.5 to 60 wt.
 of a graft polymer, based on the total weight of said composition.
- The composition of Claim 1, wherein said composition comprises:
 - A) 40 to 99 wt. % of at least one of aromatic polycarbonate and polyester carbonate;
 - B) 0.5 to 60 wt. % of a graft polymer;
 - O to 45 wt. % of at least one thermoplastic polymer selected from the group comprising of vinyl (co)polymers and polyalkylene terephthalates;

15

20

25

- D) 0.5 to 20 wt. % of said phosphorus compound represented by general formula (I); and
- E) 0 to 5 wt. % of a fluorinated polyolefin.

wherein the weight percents of A), B), C), D) and E) are each based on the total weight of said composition.

- 7. The composition of Claim 6 wherein said graft polymer B) is10 prepared from:
 - B.1 5 to 95 wt. % of at least one vinyl monomer; and
 - B.2 95 to 5 wt. % of at least one graft base having a glass transition temperature of less than 10°C,

the weight percents of B.1 and B.2 being based on the total weight of B.1 and B.2.

- The composition of Claim 7, wherein said vinyl monomer B.1 comprises a mixture of.
 - B.1.1 a first vinyl monomer selected from at least one of styrene, α-methyl styrene, p-methyl styrene, p-chlorine styrene and (meth) acrylic acid-(C₁-C₆)-alkyl esters, and
 - B.1.2 a second vinyl monomer selected from at least one of vinyl cyanides, (meth)acrylic acid -(C₁-C₈)-alkyl esters and derivatives of unsaturated carboxylic acids; and said graft base B.2 is selected from diene rubber, acrylate rubber, EP(D)M rubber and mixtures thereof.

30

20

25

- The composition of Claim 8 wherein
 said first vinyl monomer B.1.1 is styrene and said second
 vinyl monomer B.1.2 is acrylonitrile; and
- said graft base B.2 is polybutadiene, the polybutadiene optionally comprising up to 30 wt. %, based on the weight of said graft base B.2, of a comonomer selected from styrene, acrylonitrile, methylmethacrylate and mixtures thereof.
- The composition of Claim 1, further comprising at least one
 additive selected from stabilisers, pigments, mould release agents, flow auxiliary substances, antistatics, fillers and reinforcing agents.
 - 11. A moulded article prepared from the composition of Claim 1.
- 15 12. A method of improving the flame resistance of a composition comprising a thermoplastic polymer selected from at least one of polycarbonate and polyester carbonate, said method comprising incorporating into said composition a phosphorus compound represented by general formula (I),

$$R^{1} = (O) \prod_{\substack{i \in O \\ i \in O \\ R^{2}}}^{O} \bigcap_{\substack{i \in O \\ R^{2}}}^{(R^{5})_{q}} Y = (R^{6})_{q} \bigcap_{\substack{i \in O \\ i \in O \\ R^{3} = 0}}^{(R^{6})_{q}} (O) \bigcap_{\substack{i \in O \\ R^{4}}}^{R^{4}}$$
 (I),

in which

 $R^1,\,R^2,\,R^3$ and R^4 are each independently selected from (i) C_1 to C_8 alkyl optionally substituted by halogen, (ii) C_5 to C_6 cycloalkyl, (iii) C_6 to C_{10} aryl and (iv) C_7 to C_{12} aralkyl, each of (ii), (iii) and (iv)

25

being optionally and independently substituted by at least one of halogen and C_1 to C_4 alkyl;

n is 0 or 1;

5

- q is 0, 1, 2, 3 or 4;
- N is 0.1 to 5
- 10 R^5 and R^6 independently of one another are each selected from C_1 to C_4 alkyl and halogen; and
 - Y denotes isopropylidene,
- wherein the phosphorous compound represented by general formula (I) comprises less than 1 wt. % of isopropenylphenyl phosphate, based on the weight of the phosphorous compound represented by general formula (I).
 - 13. The method of Claim 12, wherein the phosphorus compound represented by general formula (I) comprises less than 0.5 wt. % of isopropenylphenyl phosphate, based on the weight of said phosphorous compound represented by formula (I).
 - 14. The method of Claim 12, wherein the phosphorus compound represented by general formula (I) comprises less than 0.2 wt. % of isopropenylphenyl phosphate based on the weight of said phosphorus compound represented by general formula (I).
- 30 15. The composition of Claim 7 wherein said graft base B.2 has a glass transition temperature of less than 0°C.

- The composition of Claim 7 wherein said graft base B.2 has a glass transition temperature of less than -20°C.
- 17. The composition of Claim 8 wherein the vinyl cyanides, of which said second vinyl monomer B.1.2 may be selected, are selected from at least one of acrylonitrile and methacrylonitrile; and the derivatives of unsaturated carboxylic acids, of which said second vinyl monomer B.1.2 may be selected, are selected from at least one of maleic acid anhydride and N-phenylmaleimide.